



Cladco Ltd

EC Declaration of Performance



1224

1	<p>Unique identification code of product type:</p> <p style="text-align: center;">Sigma Purlins in the following sizes/guages</p> <table border="0" style="width: 100%;"> <tr> <td>145mm x 65mm x 1.6mm</td> <td>225mm x 65mm x 1.6mm</td> <td>265mm x 65mm x 1.6mm</td> </tr> <tr> <td>145mm x 65mm x 2.0mm</td> <td>225mm x 65mm x 2.0mm</td> <td>265mm x 65mm x 2.0mm</td> </tr> <tr> <td></td> <td>225mm x 65mm x 2.5mm</td> <td>265mm x 65mm x 2.5mm</td> </tr> <tr> <td>175mm x 65mm x 1.6mm</td> <td></td> <td>265mm x 65mm x 3.0mm</td> </tr> <tr> <td>175mm x 65mm x 2.0mm</td> <td>235mm x 65mm x 1.6mm</td> <td></td> </tr> <tr> <td></td> <td>235mm x 65mm x 2.0mm</td> <td>300mm x 65mm x 2.0mm</td> </tr> <tr> <td>205mm x 65mm x 1.6mm</td> <td>235mm x 65mm x 2.5mm</td> <td>300mm x 65mm x 2.5mm</td> </tr> <tr> <td>205mm x 65mm x 2.0mm</td> <td></td> <td>300mm x 65mm x 3.0mm</td> </tr> </table>			145mm x 65mm x 1.6mm	225mm x 65mm x 1.6mm	265mm x 65mm x 1.6mm	145mm x 65mm x 2.0mm	225mm x 65mm x 2.0mm	265mm x 65mm x 2.0mm		225mm x 65mm x 2.5mm	265mm x 65mm x 2.5mm	175mm x 65mm x 1.6mm		265mm x 65mm x 3.0mm	175mm x 65mm x 2.0mm	235mm x 65mm x 1.6mm			235mm x 65mm x 2.0mm	300mm x 65mm x 2.0mm	205mm x 65mm x 1.6mm	235mm x 65mm x 2.5mm	300mm x 65mm x 2.5mm	205mm x 65mm x 2.0mm		300mm x 65mm x 3.0mm
145mm x 65mm x 1.6mm	225mm x 65mm x 1.6mm	265mm x 65mm x 1.6mm																									
145mm x 65mm x 2.0mm	225mm x 65mm x 2.0mm	265mm x 65mm x 2.0mm																									
	225mm x 65mm x 2.5mm	265mm x 65mm x 2.5mm																									
175mm x 65mm x 1.6mm		265mm x 65mm x 3.0mm																									
175mm x 65mm x 2.0mm	235mm x 65mm x 1.6mm																										
	235mm x 65mm x 2.0mm	300mm x 65mm x 2.0mm																									
205mm x 65mm x 1.6mm	235mm x 65mm x 2.5mm	300mm x 65mm x 2.5mm																									
205mm x 65mm x 2.0mm		300mm x 65mm x 3.0mm																									
2	<p>Name & Registered Address of Manufacturer:</p> <p style="text-align: center;">Cladco Ltd 16 Baronald Street Rutherglen Glasgow G73 1AH Tel: 0141 647 8866</p> <p style="text-align: center;">16</p> <p style="text-align: center;">1224-CPR-1061</p>																										
3	<p style="text-align: center;">BS EN 1090-1:2009+A1:2011</p> <p style="text-align: center;">Galvanised Sigma Purlins, for use in Roof Construction, in Single Span, Double Span, or Sleeved Systems Manufactured from 1.6mm, 2.0mm, 2.5mm & 3.0mm thick Hot Dipped Galvanised Steel, to BS EN 10326:2004 & BS EN 10143:1993 Minimum Grade of Steel S450GD, with Z275 Zinc Coating Execution Class EXC2</p>																										
4	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 33%;">Essential Characteristics</th> <th style="width: 33%;">Performance</th> <th style="width: 34%;">hEN</th> </tr> </thead> <tbody> <tr> <td>Nominal Thickness</td> <td>1.6mm, 2.0mm, 2.5mm & 3.0mm</td> <td>BS EN 10326:2004</td> </tr> <tr> <td>Material</td> <td>S450GD + Z275 Steel</td> <td>BS EN 10143:1993</td> </tr> <tr> <td>Reaction to fire</td> <td>Class A1</td> <td></td> </tr> <tr> <td>Load-Bearing Capacity</td> <td>In accordance with the Load/Span tables, published in the Cladco 'Purlins & Cladding rails' brochure</td> <td></td> </tr> </tbody> </table>			Essential Characteristics	Performance	hEN	Nominal Thickness	1.6mm, 2.0mm, 2.5mm & 3.0mm	BS EN 10326:2004	Material	S450GD + Z275 Steel	BS EN 10143:1993	Reaction to fire	Class A1		Load-Bearing Capacity	In accordance with the Load/Span tables, published in the Cladco 'Purlins & Cladding rails' brochure										
Essential Characteristics	Performance	hEN																									
Nominal Thickness	1.6mm, 2.0mm, 2.5mm & 3.0mm	BS EN 10326:2004																									
Material	S450GD + Z275 Steel	BS EN 10143:1993																									
Reaction to fire	Class A1																										
Load-Bearing Capacity	In accordance with the Load/Span tables, published in the Cladco 'Purlins & Cladding rails' brochure																										

The performance of the products identified in points 1 & 3 is in conformity with the performance in point 4. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 2.

Signed for and on behalf of the manufacturer by:

Name: Lewis Davie	Function: Director
Date of issue: <i>29.6.17</i>	Signature